

PAGE 1 OF 2
CITY OF ALBUQUERQUE RFB2006-050-SB
SCISSOR LIFT
FRANK'S SUPPLY

AGENCY: _____
DEPARTMENT: _____
DIVISION: _____
REQUISITION #: _____ PO #: _____

DESCRIPTION:	Scissor Lift	MAKE:	Genie
VENDOR:	Franks's Supply	MODEL:	2632
BASE COST PER UNIT:	\$ 14,250.00		
A. GENERAL			
1.	90 degree steering providing zero turning radius and easy maneuverability.		
2.	Single door access 32-inches.		
3.	On-board troubleshooting diagnostics which notify the operator of fault conditions.		
4.	Variable speed motor that efficiently uses energy needed to do the required work.		
5.	Weather resistant, impact resistant, molded joystick controller box operates from the platform or the ground.		
6.	The solid steel deck platform has a slip-resistant surface.		
7.	Heavy duty square steel guardrails fold down quickly without tools for single door access.		
8.	Low noise level allows operation in quiet work environment.		
9.	Swing-out battery box and power module allow easy access to componentry.		
10.	Lubrication-free, service-free pivot points.		
B. Standard Features			
1.	32-foot (nominal) working height.		
2.	39-inch (nominal) roll-out platform extension		
3.	Compact 32-inch (nominal) width.		
4.	500 pound lift capacity.		
5.	Proportional controls for lift and drive functions.		
6.	Automatic 25 amp battery charger.		
7.	Manual platform lowering valve.		
8.	Emergency Stop switches at both platform and ground controls.		
9.	Drive speed interlock limits speed while elevated.		
10.	Multiple disc brakes provide smooth deceleration.		
11.	Manual brake release.		
12.	Pothole guards.		
13.	Non-marking tires.		
14.	AC wiring to platform.		
15.	TILT SENSOR WITH AN AUDIBLE ALARM.		
16.	BEEPER HORN.		
17.	HOUR METER.		
C. SPECIFICATIONS			
1.	Working height:	32 feet	
2.	Platform height:	26 feet	
3.	Height stowed:	90 inches	
4.	Height stowed, rails folded:	68 inches	
5.	Platform height – stowed:	46 inches	
6.	Length – stowed:	96 inches	
7.	Length – platform extended:	135 inches	
8.	Width:	32 inches	
9.	Wheelbase:	73 inches	

PAGE 2 OF 2
CITY OF ALBUQUERQUE RFB2006-050-SB
SCISSOR LIFT
FRANK'S SUPPLY

10. Ground clearance – at machine center:	4 inches
11. Ground clearance – pothole guards deployed:	7/8 inch
12. Platform length:	89 inches
13. Platform length extended:	128 inches
14. Platform width:	31 inches
15. Toeboard height:	6 inches
16. Lift capacity:	500 pounds
17. Extension deck lift capacity:	250 pounds
18. Turning radius inside:	Zero
19. Turning radius outside:	92 inches
20. Power source:	24V (4-6V, 245AH batteries)
21. Drive speed – stowed:	2.2 mph
22. Drive speed – raised:	0.5 mph
23. Raise/lower speed:	37/24 seconds
24. Controls:	24V DC proportional
25. Tires (solid rubber, non-marking)	15-inches x 5-inches
26. Gradeability:	25%
27. Drive:	Dual front wheel
28. Multiple disc brakes:	Dual rear wheel
29. Weight – ANSI/CSA	5,150 pounds
30. Weight – CE/AS	5,520 pounds

D. Standard Compliance

1. ANSI/SIA A92.6
2. AS 1418.10
3. CE compliance option
4. CSA CAN3-B354.2-M82

E. Warranty

1. Three (3) -year warranty on hydraulic componentry.
2. One (1) -year warranty on O-rings, seals and hoses.
3. Standard manufacturer's warranty on all other components.

OPTIONS

DESCRIPTION	PRICE (quantity 1 ea.)
F. Motion alarm	\$ 95.00
G. Power inverter.	\$ 1,349.00
H. Platform swing gate.	\$ 56.00
I. Air line to platform.	\$ 372.00
J. Dual flashing beacons.	\$ 175.00
K. Automotive horn.	\$ 38.00
L. Maintenance-free batteries	\$ 1,575.00
M. EE rating.	\$ 347.00

.....
OPTIONS TOTAL \$ _____

BASE PRICE \$ 14,250.00

TOTAL COST PER UNIT \$ _____

QUANTITY _____

TOTAL COST \$ _____